

# SONALIKA

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

## WT 75



AGILE 4 CYLINDER  
ENGINE

12F+12R SYNCHROMESH  
TRANSMISSION

HEAVY LIFT  
CAPACITY

PARALLELOGRAM  
LOADER OPTION

INTEGRATED SAFETY  
HVAC CABIN (OPTIONAL)



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

**THE TOUGHEST  
PERFORMER  
«FOR YOUR FIELD»**

**WT  
75**

**SONALIKA**



FEATURES	
Model Description	SONALIKA WT 75
<b>ENGINE</b>	
Engine Type	4 Cylinder Turbo Charged Engine
HP Category	75
No. of Cylinders	4
Aspiration	Turbo Charged
Cubic Capacity (cc)	3707
Rated RPM	2200
Air cleaner	Dry Air Cleaner with Clogging Sensor
Cold Start	Yes
Max Torque (Nm)	278@1200
Exhaust	Underhood Downdraft Silencer Underhood Upward
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Double Clutch
Gearbox	12F+12R
Transmission	Synchronmesh
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	33.73@2200
Minimum Speed (Km/Hr)	1.69@2200
<b>BRAKES</b>	
Brakes	Oil Immersed Brakes
Type of actuation	Mechanical
Parking Brake	Independent Type
<b>DIFFERENTIAL LOCK</b>	
Differential lock	Yes, Foot Operated
<b>PTO</b>	
PTO (rpm)	540/540E
PTO (Actuation)	Mechanical
<b>STEERING</b>	
Steering	Power
<b>ELECTRICAL</b>	
Battery	12V, 88 AH or 110 AH
Alternator	12V, 90Amps
Seven pin trailer socket	Yes
<b>HYDRAULICS</b>	
3 point linkage	CAT-II
Stay Bars	Adjustable
Hydraulic lifting capacity	2500Kg (3000kg Optional)
Auxiliary Hydraulic circuit	2DA/2SA
Lift Rods	Yes

FEATURES	
<b>SAFETY SWITCH</b>	
Clutch Safety Switch	Yes
PTO Safety Switch	Yes
Neutral Safety Switch	Yes
<b>CAPACITY (LTRS)(+/-5%)</b>	
Fuel tank (Ltr)	64
<b>TURNING RADIUS</b>	
Without Brakes (m)	6.5
<b>TYRE</b>	
Front	11.2 - 24
Rear	16.9-30
<b>DIMENSION &amp; WEIGHT(+/-5%)</b>	
Weight(kg)	3180
Wheel Base (mm)	2350
Total Length (mm)	4330
Total Width (mm)	1910
Height (mm) up to ROPS	2775
Min. Ground Clearance (mm)	385
Front Track (mm)	1615-1910
Rear Track (mm)	1515-1805
<b>OTHERS</b>	
Fuel Indicator gauge	Yes
Front Toe Hook	Yes, inbuilt in front weight
Front & Rear Weights with Std. Ballast	Front- 30kgX2 and 24kgX4 Rear- 2X30 kg
Trailer Hitch	Swinging Drawbar
ROPS	Yes
<b>OPTIONAL FEATURES</b>	
Cabin	HVAC/Heater (Optional)
Front Mudguard	Yes

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standres product.

**DEALER STAMP**



**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221

Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.sonalika.com/www.solisworld.com